Insert NEGATIVE TYPE

● : Continuous cutting
ⓒ : Light interrupted cutting
✠ : Heavy interrupted cutting

RN

Round, with hole



		T9205	T9215	T9225	T9235	T9105	T9115	T9125	T9135	AH120	TH10	LX11
		Coated									Uncoated	Ceramic
P	Steel	●	●ⓒ	ⓒ✠	✠	●	●ⓒ	ⓒ✠	✠	●ⓒ	●	
M	Stainless		●ⓒ							●ⓒ	●	
K	Cast iron	●ⓒ	●ⓒ			●ⓒ	●ⓒ			●ⓒ	●	
N	Non-ferrous										●	
S	Superalloy									●ⓒ		
H	Hard material											●

Application	Chipbreaker	Designation	T9205	T9215	T9225	T9235	T9105	T9115	T9125	T9135	AH120	TH10	LX11	RE	IC	S	D1
Heavy cutting	61	RNMG090300-61		●	●			▲	▲					-	9.525	3.18	3.81
		RNMG120400-61	●	●	●	●	▲	▲	▲	▲	●	●		-	12.7	4.76	5.16
		RNMG150600-61		●	●			▲	▲					-	15.875	6.35	6.43
		RNMG190600-61		●	●	●		▲	▲	▲				-	19.05	6.35	7.93
		RNMG250900-61		●	●			▲	▲					-	25.4	9.52	9.22
Finishing to medium cutting	-	RNGA120400											●	-	12.7	4.76	5.16





RN

Round, without hole



		FX105	LX11	WG300
		Ceramic		
P	Steel			
M	Stainless			
K	Cast iron	●ⓒ		
N	Non-ferrous			
S	Superalloy			●ⓒ
H	Hard material		●	

Application	Chipbreaker	Designation	FX105	LX11	WG300	RE	IC	S	D1
Finishing to medium cutting	-	RNGN120400	●	●		-	12.7	4.76	-
		RNGN120700	●	●		-	12.7	7.94	-

● : Line up
▲ : To be discontinued

Reference pages: RNMG..., RNGA...:External toolholder → C080 -