CHAMFERING INSERT

XHGT-30A



XHGR-45A





XHGR-60A



P	Steel	★
M	Stainless	★
K	Cast iron	★
N	Non-ferrous	☆
S	Superalloys	★
H	Hard materials	★

★ : First choice
☆ : Second choice

Designation	W1	S	Coated GH730	Chamfering angle PNA	Maximum width of chamfer **
XHGT090300-30A	8.5	3.3	●	30°	1.5
XHGR090300-45A	8.5	3.3	●	45°	6
XHGR090300-60A	8.5	3.3	●	60°	3.5

● : Line up
2 pieces per package

**Please reduce the feed rate to half when chamfering over 60% of maximum width of chamfer.

INSERT FOR SPECIAL CHAMFERING ADAPTERS

AOMT...



AOMT**-C45



AOMT**-N-**DT



P	Steel	★
M	Stainless	★
K	Cast iron	★
N	Non-ferrous	☆
S	Superalloys	★
H	Hard materials	★

★ : First choice
☆ : Second choice

Designation	W1	S	Coated GH730	LE	Chamfering angle PNA
AOMT060204-C45	5.66	1.96	●	4.5	45°
AOMT030204-N-30DT	4	1.59	●	4	30°
AOMT030204-N-45DT	2.8	1.59	●	4	45°

● : Line up